

**New & Improved**

## **ROLOSHIELD™ The New and Improved RoloShield™ Plus, Pro, Prime & Extreme**



Contractor friendly RoloShield™ is lightweight, stronger than felt, and is faster to install. Use less rolls to cover more roof and lower your installed cost by using this 100% polypropylene synthetic roofing underlayment. RoloShield™ lays flat and is water-resistant with superior drapability in valleys and on ridges and hips. Speedy installation is achieved by using the RoloShield™ pre-printed nailing pattern. Extended UV resistance provides installation opportunities on hot sunny days and provides a cooler working surface. RoloShield™ is Class A fire rated, and Code Approved. The new and improved RoloShield™ lineup has an added slip resistant layer for every product level. With all four products having ICC and Miami-Dade approvals, the new RoloShield™ lineup offers a range of economical to high end options with code compliant quality for every product from Plus to Extreme.





**RoloShield™ Plus**  
25 Year  
Warranty

**RoloShield™ Pro**  
50 Year  
Warranty

**RoloShield™ Prime**  
Limited Lifetime  
Warranty

**RoloShield™ Extreme**  
Limited Lifetime  
Warranty



	<b>ROLOSHIELD™ PLUS</b>	<b>ROLOSHIELD™ PRO</b>	<b>ROLOSHIELD™ PRIME</b>	<b>ROLOSHIELD™ EXTREME</b>	<b>Conventional Felt 15#/30#</b>
<b>Material</b>	100% synthetic woven is the green answer to asphaltic. Manufactured from post-industrial recycled material.	100% synthetic woven is the green answer to asphaltic. Manufactured from post-industrial recycled material.	100% synthetic woven is the green answer to asphaltic. Manufactured from post-industrial recycled material.	100% synthetic woven is the green answer to asphaltic. Manufactured from post-industrial recycled material.	Asphalt
<b>Product Weight</b>	1.9 lbs per square 19 lbs per roll	2.2 lbs per square 22 lbs per roll	3.2 lbs per square 32 lbs per roll	3.8 lbs per square 38 lbs per roll	45/60 lbs per roll
<b>Quantity/ Size</b>	10 squares per roll 48" wide x 250 lineal ft	10 squares per roll 48" wide x 250 lineal ft	10 squares per roll 48" wide x 250 lineal ft	10 squares per roll 48" wide x 250 lineal ft	2 squares per roll 36" wide x 72 lineal ft
<b>Tear Resistance/ Tensile Strength</b>	20lbs/40lbs	20lbs/50lbs	20 lbs/50lbs	35lbs/90lbs	15# felt - 2lbs 30# felt - 4lbs
<b>Durability</b>	UV resistant Can be exposed for up to 6 months	UV resistant Can be exposed for up to 6 months	UV resistant Can be exposed for up to 6 months	UV resistant Can be exposed for up to 6 months	Begins to degrade immediately
<b>Warranty</b>	25 year warranty	50 year warranty	Limited lifetime warranty	Limited lifetime warranty	No Warranty
<b>Porosity</b>	Lays flat and is water resistant. Superior drapability in valleys, ridges & hips	Lays flat and is water resistant. Superior drapability in valleys, ridges & hips	Lays flat and is water resistant. Superior drapability in valleys, ridges & hips	Lays flat and is water resistant. Superior drapability in valleys, ridges & hips	Puckers and wrinkles when wet. Cracks in valleys, ridges & hips
<b>Fire Rating</b>	Class A fire rating	Class A fire rating	Class A fire rating	Class A fire rating	No fire rating
<b>Permeability</b>	0.06 perms	0.06 perms	0.06 perms	0.06 perms	
<b>Nominal Thickness</b>	6 mil	7 mil	9 mil	11 mil	
<b>Temperature Range</b>	-40°F to 240°F	-40°F to 240°F	-40°F to 240°F	-40°F to 240°F	
<b>Approvals</b>					
<b>Part Number</b>	ROLOPLUS	ROLOPRO	ROLOPRIME	ROLOEXT	
<b>Rolls/ Pallet</b>	64	56	42	36	